



*Up-to-date Questions and Answers from authentic resources to improve knowledge and pass the exam at very first attempt. ----- Guaranteed.*



H12-221 Dumps  
H12-221 Braindumps  
H12-221 Real Questions  
H12-221 Practice Test  
H12-221 Actual Questions



[killexams.com](https://killexams.com)

**Huawei**

# H12-221

*Huawei Certified Network Professional-Implementing Enterprise Routing Network*

ORDER FULL VERSION

<https://killexams.com/pass4sure/exam-detail/H12-221>



### Question: 118

When using routing policy for route filtering, which will be denied when the router prefix matching the following IP-Prefix? (Multiple Choice)

```
ip ip-prefix aa index 10 deny 0.0.0.0 24 less-equal 32
ip ip-prefix aa index 20 permit 0.0.0.0 0 less-equal 32
```

- A . 1.1.1.1/24
- B . 1.1.1.1/32
- C . 1.1.1.1/26
- D . 1.1.1.2/16

**Answer:** ABC

### Question: 119

The community attribute of the route set through routing policy, does it affect route routing?

- A . Indirectly, the route can be classified by setting the Community property of the route, and then different route routing related attributes such as Local\_Pre, MED, etc. can be set according to the category, thereby affecting the purpose of route selection.
- B . Can't be affected because the Community attribute of the route is non-transitional and can't be passed between routers.
- C . Indirectly, the route can be classified by setting the community attribute of the route, and then different route selection related attributes can be set according to the categories. These attributes can only include Local\_Pre and MED, thus affecting route selection.
- D . After the router receives a route update with the community attribute No\_Advertise, it will not be advertised outside the local A

**Answer:** A

### Question: 120

The master-slave relationship of OSPF neighbors is negotiated through DD packets.

- A . True
- B . False

**Answer:** A

### Question: 121

The following is a partial output configuration of the Huawei router. The correct description about the configuration of this part is:

```
[Huawei] bgp 100
[Huawei-bgp]peer 12.12.12.2 ip-prefix P1 export
[Huawei]ip ip-prefix P1 index 5 deny 10.0.0.0 8 greater-equal 8 less-equal 32
[Huawei]ip ip-prefix P1 index 10 deny 172.16.0.0 12 greater-equal 16 less-equal 32
[Huawei]ip ip-prefix P1 index 15 deny 192.168.0.0 16 greater-equal 16 less-equal 32
[Huawei]ip ip-prefix P1 index 20 permit 0.0.0.0 0 less-equal 32
```

- A . When the router advertises its own BGP routes to BGP neighbor 12.12.12.2, it will be allowed to advertise routes from 10.0.0.0 to 10.255.255.255.
- B . When the router advertises its own BGP routes to BGP neighbor 12.12.12.2, it will allow advertisement of routes from 172.16.0.0 to 172.31.255.255.
- C . When the router advertises its own BGP routes to BGP neighbor 12.12.12.2, it will filter out the routes from 172.16.0.0 to 172.31.255.255.
- D . When the router advertises its own BGP routes to BGP neighbor 12.12.12.2, it filters out all routes.

**Answer: C**

### Question: 122

When a router running BGP receives a route with an unreachable next hop, what should I do?

- A . Send an error message to the router that issued the Update.
- B . Refused to join the BGP routing table and silently discarded.
- C . Receive the route and add it to the BGP routing table. But this route will not be preferred by BGP and will not join the IP routing table.
- D . Receive the route, join the BGP routing table, and participate in the BGP routing rules. It may be optimized as the best route and join the IP routing table.

**Answer: C**

### Question: 123

OSPF supports multiple processes that can run multiple different OSPF processes on the same router, and they are independent of each other. Routing interactions between different OSPF processes correspond to routing interactions between different routing protocols.

- A . True
- B . False

**Answer: A**

### Question: 124

In the static LACP mode, the correct description of the active link selection is: (Multiple Choice)

- A . After a member interface is added to the Eth-Trunk in static LACP mode, the member interface sends the information negotiation active port about the system priority, system MAC address, interface priority, and interface number to the peer.
- B . The higher the system LACP priority is, the higher the priority is. At both ends of the devices, select the system with the larger LACP priority value as the active end. If the system LACP priority is the same, select the one with the higher MAC address as the active end.

- C . The passive end device determines the activity interface based on the active end interface LACP priority and interface ID (interface number).
- D . The interfaces selected by two-end device are inconsistent and the data can be forwarded normally.

Answer: AC

Question: 125

The OSFF NBMA network requires that routers in the network must select DR and BDR; otherwise, they canâ€™t work.

- A . True
- B . False

Answer: B

Question: 126

On the device running MSTP obtain the information as shown in the figure. Note that the status of the port on Ethernet 1/0/13 in Instance 1 is:

[SWC]display stp brief

| MSTID | Port           | Role | STP State  | Protection |
|-------|----------------|------|------------|------------|
| 0     | Ethernet1/0/2  | DESI | FORWARDING | NONE       |
| 0     | Ethernet1/0/3  | DESI | FORWARDING | NONE       |
| 0     | Ethernet1/0/12 | ALTE | DISCARDING | NONE       |
| 0     | Ethernet1/0/13 | ROOT | FORWARDING | NONE       |
| 1     | Ethernet1/0/2  | DESI | FORWARDING | NONE       |
| 1     | Ethernet1/0/12 | ROOT | FORWARDING | NONE       |
| 1     | Ethernet1/0/13 | ALTE | DISCARDING | NONE       |
| 2     | Ethernet1/0/3  | DESI | FORWARDING | NONE       |
| 2     | Ethernet1/0/12 | ALTE | DISCARDING | NONE       |
| 2     | Ethernet1/0/13 | ROOT | FORWARDING | NONE       |

- A . Forwarding
- B . Discarding
- C . ALTE
- D . NONE

Answer: B

Question: 127

The following is a partial configuration of a router. The correct description about this part of the configuration is:

```
ip ip-prefix p1 permit 10.0.192.0 8 greater-equal 17 less-equal 18
```

- A . On the 10.0.192.0/8 network segment, the route with a mask length of 18 will be matched to the prefix list, the matching rule is allowed.
- B . On the 10.0.192.0/8 network segment, the route with a mask length of 19 will be matched to the prefix list, the matching rule is allowed.
- C . On the 10.0.192.0/8 network segment, the route with a mask length of 20 will be matched to the prefix list, the matching rule is allowed.
- D . On the 10.0.192.0/8 network segment, the route with a mask length of 21 will be matched to the prefix list, the matching rule is allowed.

**Answer:** A

### Question: 128

In multicast network environment, if IGMPv2 hosts and IGMPv1 routers (hereinafter referred to as version 2 host and version 1 router) are co-located on the same LAN, how do they work together?

- A . version 1 router treats the IGMPv2 report as an invalid IGMP message type and ignores it.
- B . When version 1 router is a valid IGMP querier, the version 2 host must send an IGMPv1 report.
- C . When Version 2 host detects that the IGMP Querier is Version 1 router, it must always respond with the IGMPv1 report.
- D . When version 2 host leaves, it still sends an IGMP leave message, and the message can't be suppressed.

**Answer:** ABC

### Question: 129

The following statement about OSPF neighbor information:

```
[RTA]display ospf peer
      OSPF Process 1 with Router ID 1.1.1.1
          Neighbors
Area 0.0.0.0 interface 10.1.1.1(Ethernet0/0)'s neighbor(s)
RouterID: 2.2.2.2      Address: 10.1.1.2
State: Full  Mode: Nbr is Master  Priority: 1
DR: 10.1.1.1  BDR: 10.1.1.2
Dead timer expires in 35s
Neighbor has been up for 04:35:02
```

- A . The router ID of this router is 1.1.1.1
- B . The neighbor's router ID is 2.2.2.2
- C . The address of DR is 10.1.1.1
- D . This router is Master

**Answer:** D

### Question: 130

Port isolation enables the isolation of communication between different ports within the same VLAN of the same switch.

- A . True
- B . False

**Answer: A**

### Question: 131

In the same LAN, if some IGMPv1 routers exist in the LAN, IGMPv1 must be forcibly configured for all routers in the subnet to use normally.

- A . True
- B . False

**Answer: A**

### Question: 132

Port isolation provides users with more safer and more flexible networking solution.

The following description about port isolation, which is incorrect?

- A . Port isolation can be used to configure Layer 2 isolation.
- B . In the default mode, port isolation is Layer 2 isolation and Layer 3 interworking.
- C . Port isolation must be configured on the ports that need to be configured for port isolation.
- D . Port isolation command port-isolate enable specifies the port configuration in global mode.

**Answer: D**

### Question: 133

Regarding the description of IGMPv1 and IGMPv2, the correct one is: (Multiple Choice)

- A . IGMPv1 packet type does not include a leave member packets.
- B . IGMPv2 packet type includes member leave packets
- C . IGMPv1 supports universal group queries.
- D . IGMPv2 supports only general group queries.

**Answer: ABC**

### Question: 134

Compared with the OSPF protocol, which are the features of IS-IS protocol? (Multiple choices)

- A . More types of network are supported
- B . More types of areas are supported
- C . The scalability of the protocol is better

D . Less protocol packets

**Answer:** CD



# SAMPLE QUESTIONS



*These questions are for demo purpose only. **Full version** is up to date and contains actual questions and answers.*

*Killexams.com is an online platform that offers a wide range of services related to certification exam preparation. The platform provides actual questions, exam dumps, and practice tests to help individuals prepare for various certification exams with confidence. Here are some key features and services offered by Killexams.com:*



**Actual Exam Questions:** *Killexams.com provides actual exam questions that are experienced in test centers. These questions are updated regularly to ensure they are up-to-date and relevant to the latest exam syllabus. By studying these actual questions, candidates can familiarize themselves with the content and format of the real exam.*

**Exam Dumps:** *Killexams.com offers exam dumps in PDF format. These dumps contain a comprehensive collection of questions and answers that cover the exam topics. By using these dumps, candidates can enhance their knowledge and improve their chances of success in the certification exam.*

**Practice Tests:** *Killexams.com provides practice tests through their desktop VCE exam simulator and online test engine. These practice tests simulate the real exam environment and help candidates assess their readiness for the actual exam. The practice tests cover a wide range of questions and enable candidates to identify their strengths and weaknesses.*

**Guaranteed Success:** *Killexams.com offers a success guarantee with their exam dumps. They claim that by using their materials, candidates will pass their exams on the first attempt or they will refund the purchase price. This guarantee provides assurance and confidence to individuals preparing for certification exams.*

**Updated Content:** *Killexams.com regularly updates its question bank and exam dumps to ensure that they are current and reflect the latest changes in the exam syllabus. This helps candidates stay up-to-date with the exam content and increases their chances of success.*

**Technical Support:** *Killexams.com provides free 24x7 technical support to assist candidates with any queries or issues they may encounter while using their services. Their certified experts are available to provide guidance and help candidates throughout their exam preparation journey.*

For More exams visit <https://killexams.com/vendors-exam-list>  
Kill your exam at First Attempt....Guaranteed!